




Novobañera® 2a PVC



Novobañera® 2a is a profile with a smooth curve made of PVC which facilitates the cleaning and avoids the accumulation of dirt in difficult corners. It also absorbs the vibrations of the hydromassage system. This profile has complementary pieces which are available to achieve an ideal finish: internal angle and cover. It is available in white and pergamon beige finishes.

General features



Material:	PVC
Length:	1,5 - 2,5 m.l. (4ft9in - 8ft2in)
Dimensions:	a: 30 mm. (1 3/16")
Packaging:	50 u./box
Finishes:	01 - white 25 - Pergamon beige


Applications

Where to install Novobañera® 2a:


- Corners between wall and kitchen countertops.
- Perimeters in shower trays or bathtubs.
- Wall-floor/wall-wall or wall-ceiling joints, horizontally and vertically.

Complementary pieces

Novobañera® 2a has complementary pieces made of Zamak for its perfect finish.



Internal angle



Cover

Materials

PVC

Novobañera® 2a is a profile made by coextrusion of PVC-P (rigid PVC) and PVC-U (flexible PVC). PVC-U provides a perfect adaptability to corners while PVC-P is suitable, due to its rigidity, to be the piece to be placed in the tiles as a support.

PVC (polyvinyl chloride), is a polar amorphous thermoplastic polymer highly resistant to abrasion, corrosion and a wide range of chemical products. Has a good resistance to impact, low water absorption, low electrical conductivity and is dimensionally stable.

Zamak

The complementary piece of Novobañera® 2a is made of Zamak. Zamak is a non ferrous alloy of Zinc with aluminium, magnesium and copper (UNE EN 1774). It is tough, has high hardness, high mechanical strength and excellent plastic deformability.

**You can find out more information by consulting the Technical files of materials in www.emac.es*

Technical Features and tests

Fire resistance	M2 (UNE 23-727-90)	
Abrasion resistance	Very good	
Working temperature	-10°C / 60°C	
Resistance to chemical agents	Buena excepto con ácido crómico, sulfúrico y disolventes orgánicos como acetato y tolueno	AIM-PLAS



Colocación

Please, first of all clean the surface of Novobañera® 2a PVC:



1. Add abundant fix material on the back surface of Novobañera® 2a. This material could be an adhesive as silicone.
2. Introduce the fixing wing between the tiling and the bathtub or counter top, pressing firmly ensuring a good contact between both surfaces.
3. Finally, clean carefully the spare material and let it dry.

Para visualizar el vídeo capture esta imagen con su móvil (requiere software lector de códigos QR) o haga click sobre ella.

**In humid environments or in direct touch with water, it is recommended to seal the joints between Novoesocias® with silicone.*

Cleaning and maintenance

The cleaning can be done with water and detergent or specific cleaner diluted. The correct use of bleach do not affect PVC.

It is not recommended using chromic acid, sulfuric acid or organic solvents as ethyl acetate, acetone or toluene.

Technical Information

You can find out more information about the technical features of Emac®'s products by downloading their Technical File from www.emac.es

If you have any query, please contact our Technical Department in tecnico@emac.es



Indoors



Wall tiling



Flooring



Recyclable

Emac Complementos S.L. (Spain) info@emac.es // Emac America L.L.C. (FL,USA) info@emac-america.com// Emac Italia S.R.L. (Italy) info@emac-italia.it
www.emac.es

*The data provided are only for information and have been obtained by our supplier or Emac®.
Does not constitute legal guarantee in terms of properties and / or functionality of the application of material*