



Novorodapie® L



Novorodapie® L Aluminum is a skirting profile with simple design made of anodized or lacquered aluminum. Its design, with flat visible side, ends at the bottom with rounded shape which makes easier the cleaning and covers the perimeter joint, allowing the free movement of the flooring.


Available in matt silver, off white and matt black colors.

Applications

Novorodapie® L Aluminum is a baseboard profile made of anodized or lacquered aluminum. This baseboard has been designed to protect the bottom of the walls, providing a high decorative and also functional value, as it covers the perimeter joint allowing this way the free movement of the flooring.

Novorodapie® L Aluminum is easy to install by applying adhesive on the rear.

General Features



Material:	Anodized/lacquered aluminum
Length:	2,5 ml (8.2")
Dimensions:	a: 60/80/100 mm (2-3/8" 3/18" 4")
Finishes:	Matt silver-13 Off-White - 142 Matt black - 90

Technical features

Alloy:	6063 / T5	
Stress test:	110-130 MPa	EN 755-2
Tensile strength:	160-175 MPa	
Elongation (%):	8%	
Fire resistance:	M0 (UNE 23-727-90)	
Abrasion resistance:	Very good	
Corrosion resistance:	Very good	
Appearance and color:	Excellent	EN 12373-1
Anodizing /lacquering:	Qualanod seal/Qualicoat seal	

Materials



Novorodapie® L Aluminum is a profile made by aluminum extrusion. The matt silver and matt black finishes have been anodized, improving mainly through this process its corrosion resistance, mechanical resistance and appearance. The anodized applied has the quality seal Qualanod, which guarantees the quality of the process and the resulting profiles. This seal regulates several tests: appearance and color, thickness measurements, sealing and impregnation control, abrasion resistance, lightfastness, acetic saline chamber and nitric acid immersion.



The off-white finish has been lacquered, obtaining so a high quality and homogeneous surface. The lacquering has the quality seal Qualicoat, which guarantees the quality of the process and the final products.

The aluminum is a raw material with excellent chemical and physicomechanical properties. It is light, tough, ductile, malleable and highly durable. It has a great resistance to fire and corrosion.

Installation

Novorodapie® L Aluminum is an easy-to-install profile.

1. Clean the surface to install the Novorodapie® L.
2. Apply mounting adhesive or polyurethane mastic on the rear
3. Join the profile to the wall and press it to get an optimal adhesion.
4. Remove the possible leftover material and let dry.

Cleaning and maintenance

The product must be cleaned periodically with a soft cloth. If you use a neutral liquid cleaner, you must rinse the profile with cold water and dry it to remove the humidity excess. The persistent dirtiness can be removed by using cleaning approved agents lightly abrasive or a grid covered with polished powder neutral.

Steel wool, abrasive cleaners, souring products as well as strong acids (hydrochloric and perchloric), strong bases (caustic soda or ammonia) or carbonated solutions are not recommended. Citric acid is neither recommended because it dissolves the protective layer of the surface of aluminium. Waxes, petrolatum, lanolin or similar substances are not appropriate. Solvents containing haloalkanes (hydrofluoroether and chlorinated solvents) and curing accelerators containing chlorides should not be used (use special accelerators free of chlorides).

Technical information

You can find out more information about the technical features of Emac®'s products by downloading its Technical File in www.emac.es.

If you have any query, please contact our Technical Department in tecnico@emac.es.



ESTERNO
OUTDOOR
ESTERNO



INTERNO
INDOOR
INTERNO



PANNELLI
PANELS
PANELE



RICICLABILE
RECYCLABLE
RICICLABILE