




Novobañera® 2b PVC



Profile of smooth curve made with PVC which facilitates the cleaning and avoids the accumulation of dirt in difficult corners. It also absorbs the vibrations of the hydromassage system. Novobañera® 2b helps to fulfill with the Spanish Standard UNE-EN 14516:2006. This profile has complementary pieces which are available to achieve a perfect finish: internal angle and cover. It is available in white finish.

General features



Material:	PVC
Length:	1,5 - 2,5 m.l. (4ft9in - 8ft2in)
Dimensions:	a: 28 mm. (1 1/16")
Packaging:	100 u./box
Finishes:	01 - White

Applications

Where to install Novobañera® 2b:

- Corners between wall and kitchen countertops.
- Perimeters in shower trays or bathtubs.
- Wall-floor/wall-wall or wall-ceiling joints, horizontally and vertically.

Novobañera® 2b helps to fulfill with the Spanish Standard UNE-EN 14516:2006 which specifies the requirements and procedure to evaluate the compliance of bathtubs for domestic use and personal hygiene.

Complementary pieces

Novobañera® 2b has complementary pieces to get a perfect finish.



Internal angle



Cover

Materials



Novobañera® 2b is a profile made by coextrusion of PVC-P (rigid PVC) and PVC-U (flexible PVC). PVC-U provides a perfect adaptability to corners while PVC-P is suitable, due to its rigidity, to be the piece to be placed in the tiles as a support.

PVC (polyvinyl chloride), is a polar amorphous thermoplastic polymer highly resistant to abrasion, corrosion and a wide range of chemical products. Has a good resistance to impact, low water absorption, low electrical conductivity and is dimensionally stable.

Technical Features and tests

	Fire resistance	M2 (UNE 23-727-90)	
	Abrasion resistance	Very good	
	Working temperature	-10°C / 60°C	
	Resistance to chemical agents	Buena excepto con ácido crómico, sulfúrico y disolventes orgánicos como acetato y tolueno	AIMPLAS

Installation

Please, clean the surface to install Novobañera® 2b.

1. Cover generously the back face of Novobañera® 2b with an adhesive silicone.
2. Fill also the posterior cavity with the same adhesive to ensure a perfect sealing and good grip.
3. Place the Novobañera® 2b on the corner and press firmly ensuring a good contact between both surfaces.
4. Finally clean the remaining material and let dry.

** In humid environments or in direct touch with water, it is recommended to seal the joints between Novobañera® with silicones.*

Cleaning and maintenance

The cleaning can be done with water and detergent or specific cleaner diluted. The correct use of bleach do not affect PVC.

It is not recommended using chromic acid, sulfuric acid or organic solvents as ethyl acetate, acetone or toluene.

Technical information

You can find out more information about the technical features of Emac®'s products by downloading its Technical File in www.emac.es.

If you have any query, please contact our Technical Department in tecnico@emac.es.



Indoors



Wall tiling



Flooring



Recyclable

Emac Complementos S.L. (Spain) info@emac.es // Emac America L.L.C. (FL,USA) info@emac-america.com // Emac Italia S.R.L. (Italy) info@emac-italia.it
www.emac.es

*The data provided are for information only and have been obtained by our supplier or Emac®.
Does not constitute legal guarantee in terms of properties and / or functionality of the application of material*