



## Novosepara® MINI


Embellisher transition profile from **EMAC®'s MINI Collection**, made of aluminum and designed to be installed as a floor separator between same or different kind of low-thickness floorings. In addition to its reduced visible side, only 15 mm, it has a fixing wing less than 5 mm, which allows it to be installed in multiple thicknesses both before and after installing the floor. Available in matt silver and matt black finishes.

### Applications

**Novosepara® MINI** is a decorative profile that acts as floor separators in floors of all types of thickness, specially low-thickness floors such as ceramic, vinyl or carpet.

### General features

Material:	Aluminium
Length:	2,5 ml (8'2")
Dimensions:	a: 15 mm (9/16") h: 4,7 mm (3/16")
Packaging:	20 u/box
Finishes:	



Matt silver - 13



Matt black - 90

### Technical Features and tests

Alloy:	6063 / T5	
Stress test:	110-130 MPa	EN 755-2
Tensile strength:	160-175 MPa	
Elongation (%):	8%	
Fire resistance:	M0 (UNE 23-727-90)	
Abrasion resistance:	Very good	
Corrosion resistance:	Very good	
Appearance and color:	Excellent	EN 12373-1
Anodizing:	Qualanod seal	

### Materials

**Novosepara® MINI** is a profile made by extrusion of aluminum. The anodizing process improves the corrosion resistance, mechanical resistance and appearance of profiles. It has the quality seal Qualanod, which guarantees the quality of the process and the resulting profiles. This seal regulates several tests: appearance and color, thickness measurements, sealing and impregnation control, abrasion resistance, lightfastness, acetic saline chamber and nitric acid immersion.



The aluminum has excellent chemical, physical and mechanical properties. It is lightweight, tough, ductile, malleable and highly durable

### Installation

1. Spread a big amount mortar adhesive on the surface to be tiled.
2. Do the tiling and leave the gap to install Novosepara® MINI
3. Fill the gap with adhesive and insert the profile. Be sure the visible side overlaps the flooring edge.
4. Finally, clean the leftover material and let dry.

### Cleaning and maintenance

The product must be cleaned periodically with a soft cloth. If you use a neutral liquid cleaner, you must rinse the profile with cold water and dry it to remove the humidity excess. The persistent dirtiness can be removed by using cleaning approved agents lightly abrasive or a grid covered with polished powder neutral.

Steel wool, abrasive cleaners, souring products as well as strong acids (hydrochloric and perchloric), strong bases (caustic soda or ammonia) or carbonated solutions are not recommended. Citric acid is neither recommended because dissolves the protective layer of the surface of aluminium. Waxes, petrolatum, lanolin or similar substances are not appropriate. Solvents containing haloalkanes (hydrofluoroether and chlorinated solvents) and curing accelerators containing chlorides should not be used (use special accelerators free of chlorides).

### Technical information

You can find out more information about the technical features of Emac®'s products by downloading their Technical File from [www.emac.es](http://www.emac.es)

If you have any query please contact our Technical Department in [tecnico@emac.es](mailto:tecnico@emac.es)



Emac Complementos S.L. (Spain) [info@emac.es](mailto:info@emac.es) // Emac America L.L.C. (FL,USA) [info@emac-america.com](mailto:info@emac-america.com) // Emac Italia S.R.L. (Italy) [info@emac-italia.it](mailto:info@emac-italia.it)  
[www.emac.es](http://www.emac.es)

*The data provided are for information only and have been obtained by our supplier or Emac®.  
Does not constitute legal guarantee in terms of properties and / or functionality of the application of material*